

Material datasheet

Product Multipurpose Labels white
SAP Code 2433

Facematerial		
Material description	Woodfree, white machine finished paper The paper is FSC certified mixed credit	
Printer suitability	Ink jet, laser, copier, flexography, letterpress, offset and screenprint	
Thickness	91 µm	
Grammage	70 g/m ²	
Adhesive		
Description	Acrylic, water based adhesive	
Performance	Special designed product for office documentation, address labelling, logistics and industrial applications. The research centre ISEGA has permitted that the adhesive can be used in direct contact with dry and wet, non fatty foodstuffs.	
Bonding	Universal permanent adhesive for A4 application.	
Liner		
Description	white kraft paper wood free	
Thickness	54 µm	
Grammage	51 g/m ²	
Laminate		
Thickness	148 µm	
Grammage	144 g/m ²	
Service temperature	- 20 °C / + 100 °C no negative influence with a short-time higher temperature e.g. during printing on a laser printer	
Min. application temperature	5°C	
Opt. storage conditions	20°C and 50 % RH	
Shelf life	From the date of manufacture 4 years as opt. storage conditions	
Physical parameter		
Whiteness (CIE) %	ISO 11475	164
Opacity (%)	ISO 2471	92
Packaging		
Material	100/200-sheet-pack F Flute recycled, 430 g/m ² 25-shett-pack: GD2 Recycled, 400 g/m ²	
Recycling		
Face / liner	All components use environment friendly components. The liner is neutral, does not contain dangerous or water contaminating components and can be added to the paper recycling process	
Packaging	Recyclable	

N.B.: All data to be considered as typical values