


Nuvoletta OTC Professional O-NT2463HS / O-NT2473HS

PRODUCT	DIMENSIONS	O-NT2463HS	O-NT2473HS
	Seat depth from lumbar support Seat depth Seat width Backrest height from seat Backrest height adjustment Backrest width Seat height	330-385 mm 414 mm 460 mm 410-480 mm 77 mm 326 mm 500-700 mm	330-385 mm 414 mm 460 mm 410-480 mm 77 mm 326 mm 620-870 mm
TECHNICAL DESCRIPTION			
Seat	Internal structure in multilayered beech wood anatomically shaped, 12 mm thickness. Low formaldehyde emission according to class E1. Woods certificated 100%FSC.		
Backrest	Internal structure in multilayered beech wood anatomically shaped, 10 mm thickness. Low formaldehyde emission according to class E1. Woods certificated 100%FSC.		
Padding	Seat in PU-Flex, 60 mm thickness and 40 g/L density Backrest in PU-Flex, 25 mm thickness and 50 g/L density Backrest in PU-Flex, 15 mm thickness and 40 g/L density Self-extinguishing material according to UNI 9175, recyclable and without CFC/HCFC.		
Upholstery	MIRAGE (ANTIBACTERIAL) Composition: 100% FR polyester Weight: 460 g/lm Abrasion: UNI EN ISO 12947 (> 100,000 Martindale cycles) Flammability: EN 1021-1+2; UNI 9175 (Class 1IM), DIN 4102 (B1), BS 5852 Crib 5, ÖNORM B3825 (B1), ÖNORM 3800-1 (Q1), M1, NF D 60-013 (AM18), California TB 117 Antibacterial activity test AATCC 100:2012, ASTM E2149-13a Colours: Black 724 / Dark grey 739 / Dark blue 734 / Red 721		
	VALENCIA (ANTIBACTERIAL) Composition: outside 100% PVC, inside 100% polyester Hi-Loft2™ Weight: 890 g/lmt Abrasion: DIN EN ISO 12947-2 (> 300.000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1+2, DIN 4102 (B2), ÖNORM B3825 (B1), ÖNORM A3800-1 (Q1) Bacterial resistance according to AATCC TM147 Resistant to disinfectants, blood and urine Colours: Titanium 4007, white 4008		
	BLOOM Composition: 85% PVC, 15% polyester Weight: 550 g/m2 Abrasion: UNI EN ISO 12947-2 (> 50,000 Martindale cycles) Colors: Black 124 / Grey 127 / Royal Blue 126 / Red 121		
	PLANET Composition: 87.5% PVC, 12.5% cotton Weight: 900 g/m ² Abrasion: EN ISO 5470-2 (>200,000 Martindale cycles) Flammability: UNI 9175 (Class 1IM), EN 1021-1, BS 5852-1 Crib 5 Colors: Black 114		
Mechanism	AS3: A-SYNCHRON TRI-LEVER, backrest inclination of 12° positive and 28° negative, seat of 5° positive and 3° negative, lockable in all positions. With combined activation of tilting mechanism and backrest inclination.		

	Knob activated backrest height adjustment. According to UNI EN 1335-3.
Lift action	Central piston (Ø 28 mm) with tapered connection and head control, protected by a steel tube (Ø 50 mm), black finish. Class 4 testing. Approved according to DIN 4550.
Base	0902P: base a 5 razze (Ø 600 mm) in nylon e fibra di vetro con nervature di rinforzo interne e anello in acciaio annegato nell'innesto conico, finitura nera. Omologato secondo norme ANSI/BIFMA X5.1 e UNI EN 1335-3.
Castors	0351: Conductive glides in black nylon (h 55 mm / Ø 50 mm). Instead of castors.
ACCESSORI	
M-0311	Swivel and self-braking castors (Ø 50 mm), black reinforced nylon with non-marking polyurethane ring. Instead of glides
M-0902C	5-star base (Ø 528 mm) in die-cast aluminium with internal reinforcement ribs, brushed and polished finish.
EL200	Lateral swing of the seat.
0700	Circular footrest (Ø 460 mm) with chromed steel crown and black painted steel supports, height adjustable by knob.
TEST	
UNI EN 1335-1-2	
EN 1728	
EN 1022	

Rev. 0	10-03-2025	OTC Professional :O-NT2463HS / O-NT2473HS	Page 1 of 1
--------	------------	---	-------------