

DOXA

TDS

2026-09-09

Article number	81092
Article	Stretchfolie 20MCMP 502g
Product description	Polyethylene machine film
Width (testing method measuring tape)	500 mm +/- 5 mm
Length (testing method high speed encoder)	1800 m +/- 5 m
Thickness	20 micron +/- 1 micron
Density (testing method ASTM D-1505)	0,91-0,92 g/cm ³
Rolls per pallet (europallet)	30
Roll weight	17,5
Pallet weight	525
Total pallet height (incl. pallet) mm	1180
Ultimate stretch (testing method ESTL FPT 750)	Up to 290 %
Ultimate force (testing method ESTL FPT 750)	Up to 147 Newton
Puncture test (testing method ESTL FPT 750)	Maximum 43,8 Newton, Displacement 98,4 mm
Tear test (testing method ESTL FPT 750)	Time to breakage 13,47 seconds
Recycable	100 %
Doxa Plast AB is following the norm SS-EN ISO 9001:2008.	

The shown data are indicative values: Doxa Plast AB reserves the right to modify them in accordance with the product development.

PACKAGING

- THE PALLET IS FIRMLY WRAPPED WITH STRETCHFILM. PALLET DIMENSIONS 800 x 1200 MM

LABELLING

- EACH PALLET IS MARKED WITH
- ORDER NUMBER
- ARTICLE NUMBER
- DIMENSIONS