3M Scotch-Brite™

Red Floor Pad

For daily cleaning and spray cleaning operations



Technical data sheet

TD102

Date: August 2011 Supersedes: May 2011 Author: FG

Durability: 15 000 sqm at 150

rpm.

Description:

The 3M Scotch-BriteTM Red Floor Pad is a premium quality floor maintenance pad. It's made of high quality synthetic fibre, in an open textured non-woven construction. Polishing particles are dispersed throughout the thickness and bonded with a durable adhesive. Each floor pad has a pre-cut centre

Special Features:

- Designed for cleaning and spray cleaning operations.
- Open web construction to collect soil from floors
- Fine fibre mix for effective removal of marks and fast polishing action on floors
- Flexible pad for easier washing after use
- Consistent performance
- Durable pad at work.
- Limited removal of floor finish

Where and When to Use:

THE CONTRACT OF THE CONTRACT O					
RPM	150-400	>400			
Strip					
Scrub					
Spray	XX	X			
Scrub-	XX				
ber dry-					
er					
Buff	X	X			

XX Designed for X suitable

Use the 3M Scotch-Brite[™] Red floor pad for routine spray cleaning with standard or high speed floor machines (150 - 400 RPM). It will clean and increase shine on most surfaces.

Use the 3M Scotch-BriteTM Red floor pad for routine cleaning under scrubber dryer.

Directions for Use: Spray Cleaning

- 1. Install a clean floor pad under the machine pad holder.
- 2. Dust mop entire floor area if necessary.
- 3. Spray cleaning chemical moderately on a section of floor.
- 4. Clean and buff the floor with 4 to 6 passes.
- 5. Proceed to next section of floor
- 6. Dust mop entire floor area if necessary.

Remove and wash after use.

Directions for Use: Cleaning under scrubber-dryer

- 1. Install a clean floor pad under the machine pad holder.
- 2. Clean the floor on a regular basis with 1 or 2 passes.

Remove and wash after use.

Maintenance of pad:

- 1. Remove pad from machine after each use
- 2. Fold and scrub with a nylon brush under tap water, or spray hose both sides, or machine wash
- 3. Hang up for drying. Note: Recommended washing-machine temperature is 40°C.

Performance Advantages:

Produces up to 30% more shine on protected floors. Removes more black marks. Lasts up to 2 times longer. (3M lab tests).

Product Specifications:

3M Scotch-BriteTM Red Floor Pads consist of polyester fibres and synthetic adhesives. They are not significantly affected by water and common detergents.

Product Characteristics:

Colour: Red

Marking: Black 3M Scotch-

BriteTM logo.

Thickness: 28 mm

Centre hole: Pre-cut at 85 mm Weight: 1420 g/m²

Fibre type: Polyester, mixture of

sizes.

Aggressiveness (Schiefer Value):

Expected value for spray cleaning operation: 0 to 0.17 g. 3M value: 0,1 gram

-		-, 0			
0	0,5	1	1,5	2	2,5

Sizes:

Standard and non-standard sizes available on demand.

Packaging and labelling:

Packaging material made of 100% recycled material.

Disposal Informations:

Discard into appropriate container, for incineration, if available. Packaging material: recyclable

Origin:

Made in France, in an ISO 9001:2008 and ISO 14001:2004 certified plant.

3M Commercial Care Laboratory Europe

3M France – Customer Technical Center (CTC) 95250 Beauchamp - France